



**MI**<sup>®</sup> WINDOWS  
and DOORS

## V2000 Single-hung window

MODELS 1355 & 4300

Popular with builders, contractors, and homeowners, these single-hung windows merge aesthetic qualities with energy-efficient attributes. Combining a traditional brickmould exterior and timeless color options with optimally placed metal reinforcements and a constant-force balance system, these single-hung windows provide beauty and long-lasting strength and performance for new and existing homes.



### What you can expect

#### ENERGY-EFFICIENCY

Our dual-pane insulated glass helps save on heating and cooling costs while enhancing home comfort.

- In cool weather, it provides outstanding thermal performance to eliminate cold spots near windows.
- In warm weather, insulated glass reduces solar heat gain and minimizes interior glare.

#### CONVENIENCE AND STYLE

- Brickmould exterior profile creates timeless appeal
- Surface-mounted, forced-entry-resistant locks provide a stronger, safer seal
- Full-length lift rail and constant-force balance system for easy opening and closing
- Tilt-in bottom sash for easy cleaning
- True-sloping sill optimizes water drainage and eliminates need for weep holes
- Easy sash and fixed glass removal for efficient drywall pass through during construction
- Optional window operating control device for enhanced safety



## Engineered to perform

- Welded, multi-chamber frame and sash
- Metal-reinforced lock rail and bottom sash
- Available frame styles: mounting fin, finless
- 3 1/4" frame depth
- Integral J-channel
- Available with 3 1/2" flat casing and factory-applied drywall returns
- Wood extension jambs available for 4 9/16" and 6 9/16" wall depths

## Min and max sizing

WIDTH		HEIGHT	
MIN	MAX	MIN	MAX
16 1/4"	48"	23"	78"
CONTINUOUS HEAD & SILL (CHS)* MAX			
Twin (Each Window)	37 3/4"	74"	
Twin (Overall Unit)	75 5/8"	74"	
Triple (Each Window)	35 3/4"	74"	
Triple (Overall Unit)	108"	74"	

Available in 1/8" increments. DP upgrade required for any unit greater than 84" tall. CHS available on XX, OO, XXX, and OOO configurations.

## Energy efficient glass

Optional tempered glass adds additional strength and obscure or rain glass allows light in while protecting privacy.

GLAZING TYPE	U-VALUE	SHGC	STC
Low-E glass	0.33	0.28	29
Low-E glass with grids	0.33	0.25	29
Argon and Low-E glass	0.29	0.28	29
Argon and Low-E glass with grids	0.29	0.25	29
HP Low-E glass	0.33	0.23	29
HP Low-E glass with grids	0.33	0.20	29
Argon and HP Low-E glass	0.30	0.22	29
Argon and HP Low-E glass with grids	0.30	0.20	29
Northern ENERGY STAR® Low-E glass	0.30	0.53	29
Northern ENERGY STAR® Low-E glass with grids	0.30	0.47	29

Note: all values based on standard 3/4" dual-pane insulated glass unit unless noted otherwise



**V2000 SINGLE-HUNG**  
See additional product and warranty information online.



## Create a customized look

Enhance your home's spaces with a variety of finish options and grid configurations.

### FINISH OPTIONS

#### EXTERIOR



#### INTERIOR



### COMMON GRID TYPES



Flat Grids-Between-the-Glass



Sculptured Grids-Between-the-Glass



Simulated Divided Lite

◊ Exterior paint not available with clay interior



Build boldly by choosing a range of MI window and door styles with expansive views, contemporary framing and hardware.

[miwindows.com/V2000](http://miwindows.com/V2000)